TECHNICAL CHARACTERISTICS

wineo 400 to glue – 2023

Heterogeneous resilient-flooring to glue - Covering type according to EN ISO 10582

wineo

	wood XS	wood L	wood XL	stone L
Format	610 x 122 mm	1200 x 180 mm	1505 x 235 mm	610 x 305 mm
Product thickness	2 mm	2 mm	2 mm	2 mm
Planks, tiles / m² per box	24 / 1.79 m²	18 / 3.89 m²	12 / 4.24 m²	16 / 2.98 m²
Boxes / m² per pallet	140 / 250.60 m²	60 / 233.40 m²	60 / 254.40 m²	84 / 250.32 m²
Guarantee	You can find our guarantee conditions at - www.wineo.de			



Classification

Utilization class 23 EN ISO 10874	Domestic area with intensive usage
Utilization class 31 EN ISO 10874	Commercial sector with low or occasional usage
Wear layer binder content EN ISO 10582	Typ I
Anti slip category EN 16165	R 10
Staining and chemical resistance EN ISO 26987	Good resistance according to the concentration and residence time
Light fastness EN ISO 105-B02	Light fastness (procedure 2) ≥ 6
Residual indentation EN ISO 24343-1	≤ 0.1 mm without underlay mat ~ 0.17 mm with singleGLUE
Thermal resistance EN 12667	0.011 (m²K)/W without underlay mat 0.021 (m²K)/W with singleGLUE or silentPLUS
Impact sound reduction EN ISO 16251-1	~ 4 dB without underlay mat ~ 17 dB with silentPLUS
Dimensional stability EN ISO 23999	≤ 0,15 %
REACH	free from SVHC substances ≥ 0.1 %
Disposal	Private: Possible with normal domestic refuse Commercial: Refuse-key-no. AVV 170203

Product composition

1	**Top element** Surface texture, surface seal, wear layer and decor film
2	**Base layer**
3	**Backing**
	bevelled edge - 4-sides

TÜV PROFI CERT product 70 710 4061-6 www.proficert.com

emissionsgeprüft schadstoffgeprüft PREMIUM

CE
- 25 -
Windmöller GmbH
Charles-Lindbergh-Ring 13
D-32756 Detmold
DOP: 0301010
EN 14041:2004 / AC2006
1658
B_{fl}-s1 DS E1 HCHO ≤ 2 kV ≥ 0,15 W/(mK)
www.wineo.de

ÉMISSIONS DANS L'AIR INTÉRIEUR
A+
A+ A B C

Information representative des emissions dans l'air interieur des substances volatiles presentant un risque de toxicite par inhalation, sur une echelle de classe allant de C (fortes emissions) a A+ (tres faibles emissions)

Phthalat frei – Phthalate free

factorymade coated

Relevant information:

- Underfloor heating: Suitable for all conventional hot water underfloor heating and electrical systems regulated up to a surface temperature of 29° C.
- Cleaning and care: see separate cleaning & care instruction.
- Technical subjects can be changed by Windmöller GmbH.