















TECNICAL CHARACTERISTICS


wineo 600 Rigid

Heterogeneous resilient-flooring for glueless installation - Covering type according to DIN EN 16511

wineo

	wood	wood XL	stone XL	
Format	1212 x 186 mm	1507 x 234 mm	748 x 477 mm	
Product thickness	5 mm	5 mm	5 mm	
Planks, tiles / m² per box	8 / 1.80 m ²	6 / 2.12 m ²	6 / 2.14 m ²	
Boxes / m² per pallet	56 / 100.80 m ²	48 / 101.76 m ²	44 / 94.16 m ²	
Guarantee Extended warranty	20 years for private use according to Windmüller warranty conditions - www.wineo.de + 5 years for laying on PU underlay mat			

Classification			Product composition	
	Utilization class 23 EN ISO 10874	Domestic area with intensive usage	1	Surface seal
	Utilization class 32 EN ISO 10874	Commercial sector with average usage	2	Surface texture Various embossings
	Wear layer binder content EN ISO 10582	Typ I	3	Wear layer Thickness 0.4 mm
	Anti slip category DIN 51130	R 9	4	Design Decor film
	Resistance to staining EN 438-2	Group 1 + 2: grade 5 Group 3: grade 4	5	Elastic top layer
	Light fastness EN ISO 105-B02	Light fastness (procedure 2) ≥ 6	6	Core board
	Residual indentation EN ISO 24343-1	≤ 0.1 mm	7	Profile connection Connect technology 
	Thermal resistance EN 12667	~ 0.05 (m ² K)/W without underlay mat ~ 0.06 (m ² K)/W with silentRIGID	8	Elastic bottom layer
	Castor chair test ISO 4918	25000 revolutions no damage with rolls type W	9	Underlay material silentRIGID (available separately)
	Anti-static properties EN 1815	≤ 2 kV		wood - Bevelled edge wood XL - registered embossed surface - Bevelled edge stone XL - real joint
	Impact sound reduction EN ISO 16251-1	~ 6 dB without underlay mat up to 13 dB with silentRIGID		
	Dimensional stability EN ISO 23999	~ 0.1 %		
	REACH	free from SVHC substances ≥ 0.1 %		
	Disposal	<u>Private:</u> Possible with normal domestic refuse <u>Commercial:</u> Refuse-key-no. AVV 170203		



Relevant information:

- Underfloor heating: Suitable for all conventional hot water underfloor heating and electrical systems regulated up to a surface temperature of 27° C.
- Cleaning and care: see separate cleaning & care instruction.
- Technical subjects can be changed by Windmüller GmbH.