

TECHNICAL CHARACTERISTICS

wineo Performance laminate flooring / Rock'n'Go

Direct Pressure Laminate flooring acc. to EN 13329 for glueless installation

wineo

Format	1288 x 195 mm	
Product thickness	9 mm	
Panels / m² per box	8 / 2.01 m ²	
Boxes / m² per pallet	48 / 96.48 m ²	
Guarantee	30 years – Guarantee for private use according to Windmüller warranty conditions – www.wineo.de	

Classification		Product composition	
Utilization class 23 EN ISO 10874	Domestic area with intensive usage	1	Surface texture various embossings
Utilization class 33 EN ISO 10874	Commercial sector with heavy usage	2	Wear layer Melamine resin overlay
AC5 Abrasion resistance EN 13329, annex E	AC5	3	Decor Decor paper
Impact resistance EN 13329-2016, annex H	Small-diameter ball test ≥ 15 N Large-diameter ball test ≥ 1000 mm	4	Core board highly compressed core board
Resistance to staining EN 438	Group 1 + 2: grade 5 Group 3: grade 4	5	Profile connection Fold-Down
Swelling value (Windmüller factory measurement)	after 24 hrs. ≤ 5 %	6	Profile seal Aqua-Stop profile seal
Residual indentation EN ISO 24343-1	Residual indentation ≤ 0.05 mm	7	Backing Melamine resin
Effect of a furniture leg EN 424	Foot type 0 – no visible change	8	Layer Sound-Stop Layer with protective film
Castor chair test EN 425	25000 revolutions no damage with rolls type W		Authentic joint design V4 – selected decors
Thermal resistance EN 12667	0.06 (m ² K)/W		 www.blauer-engel.de/uz176
Impact sound reduction acc. ISO 717-2 Walking sound reduction – glued Walking sound reduction - not glued	17 dB 17.7 sone / up to 55 % 14.1 sone / up to 44 %		
Light fastness EN ISO 105-B02	Light fastness (method 2) ≥ 6		
REACH	free from SVHC substances ≥ 0.1 %		
Disposal	<u>Private:</u> like laminated furniture; possible with normal domestic refuse <u>Commercial:</u> Refuse-key-no. AVV 170201		 PREMIUM tested for emissions, harmful substances

Windmüller GmbH
 Nord-West-Ring 21
 D-32832 Augustdorf
 DOP: 0101010
 EN 14041:2004 / AC2006
 1658
 - 18 -

 www.wineo.de

ÉMISSIONS DANS L'AIR INTÉRIEUR*

 Information représentative des émissions dans l'air intérieur des substances volatiles présentant un risque de toxicité par inhalation, sur une échelle de classe allant de C (fortes émissions) à A+ (très faibles émissions)

PREMIUM
 tested for emissions, harmful substances

Relevant Information:

- LA149SYSV4 / Dancing in the Dark = AC4 / NK 32
- Walking noise reduction measured according to Windmüller works standard, Detmold site, based on EPLF WD 021029-5
- Underfloor heating: In conjunction with suitable underlay material, suitable for all conventional hot water underfloor heating and electrical systems regulated up to a surface temperature of 27° C.
- Cleaning and care: see separate cleaning & care instruction.
- Technical subjects can be changed by Windmüller GmbH.