

# wineo Performance laminate flooring / Rock'n'Go

Direct Pressure Laminate flooring acc. to EN 13329 for glueless installation

# wineo

<b>Format</b>	1288 x 195 mm	
<b>Product thickness</b>	9 mm	
<b>Panels / m<sup>2</sup> per box</b>	8 / 2.01 m <sup>2</sup>	
<b>Boxes / m<sup>2</sup> per pallet</b>	48 / 96.48 m <sup>2</sup>	
<b>Guarantee</b>	25 years – Guarantee for private use according to Windmüller warranty conditions – <a href="http://www.wineo.de">www.wineo.de</a>	

Classification		Product composition	
<b>Utilization class 23</b> EN ISO 10874	Heavy-duty use in the domestic area	1	<b>Surface texture</b> various embossings
<b>Utilization class 33</b> EN ISO 10874	Heavy-duty use in the commercial sector	2	<b>Wear layer</b> Melamine resin overlay
<b>AC5</b> Abrasion resistance EN 13329, annex E	AC5	3	<b>Decor</b> Decor paper
Impact resistance EN 13329-2016, annex H	Small-diameter ball test $\geq 15$ N Large-diameter ball test $\geq 1000$ mm	4	<b>Core board</b> HDF
Resistance to staining EN 438	Group 1 + 2: grade 5 Group 3: grade 4	5	<b>Profile connection</b> Fold-Down
Light fastness EN ISO 105-B02	Light fastness (method 2) $\geq 6$	6	<b>Profile seal</b> Aqua-Stop profile seal
Residual indentation EN ISO 24343-1	Residual indentation $\leq 0,05$ mm	7	<b>Backing</b> Melamine resin
Effect of a furniture leg EN 424	Foot type 0 – no visible change	8	<b>Layer</b> Sound-Stop Layer with protective film
Castor chair test EN 425	25000 revolutions no damage with rolls type W		<b>Authentic joint design</b> V4 – selected decors
Thermal resistance EN 12667	0,06 (m <sup>2</sup> K)/W		
Sound-Stop Impact sound reduction acc. ISO 717-2 Walking sound reduction – glued Walking sound reduction - not glued	17 dB 17,7 sone / 55,31 % 14,1 sone / 44,06 %		
Disposal	<u>Private:</u> like laminated furniture; possible with normal domestic refuse <u>Commercial:</u> Refuse-key-no. AVV 170201		

**CE** - 18 -

Windmüller GmbH  
Nord-West-Ring 21  
D-32832 Augustdorf

DOP: 0101010  
EN 14041:2004 / AC2006  
1658

C<sub>s1</sub> DS E1  $\leq 2$  kV  $\geq 0,07$  W/(mK)

[www.wineo.de](http://www.wineo.de)

**ÉMISSIONS DANS L'AIR INTÉRIEUR\***

**A+**

A+ A B C

Information représentative des émissions dans l'air intérieur des substances volatiles présentant un risque de toxicité par inhalation, sur une échelle de classe allant de C (fortes émissions) à A+ (très faibles émissions)

**Relevant Information:**

- LA149SYSV4 / Dancing in the Dark = AC4 / NK 32
- Walking noise reduction measured according to Windmüller works standard, Detmold site, based on EPLF WD 021029-5
- Underfloor heating: In conjunction with suitable underlay material, suitable for all conventional hot water underfloor heating and electrical systems regulated up to a surface temperature of 27° C.
- Cleaning and care: see separate cleaning & care instruction.
- Technical subjects can be changed by Windmüller GmbH.