

# TECHNICAL CHARACTERISTICS

wineo 700 L		Direct Pressure Laminate flooring according to EN 13329 for glueless installation		wineo	
<b>Format</b>	wineo 700 L 1380 x 244 x 8 mm				
<b>Joint</b>	V4 joint				
<b>Panels / m<sup>2</sup> per box</b>	8 / 2.694 m <sup>2</sup>				
<b>Boxes / m<sup>2</sup> per pallet</b>	42 / 113.138 m <sup>2</sup>				
<b>Guarantee Guarantee extension</b>	25 years for private use according to Windmüller guarantee conditions – www.wineo.de + 5 years when installed on PU Underlays				
<b>Classification</b>		<b>Product composition</b>			
<b>Utilization class 23</b> EN ISO 10874	Domestic area with intensive usage	1	<b>Surface texture</b> registered embossed		
<b>Utilization class 32</b> EN ISO 10874	Commercial sector with average usage	2	<b>Wear layer</b> Melamine resin overlay		
<b>Abrasion resistance</b> EN 13329, annex E	AC5	3	<b>Decor</b> Decor paper		
<b>Impact resistance</b> EN 17368d, Anhang H	Small-diameter ball test ≥ 35 N Large-diameter ball test ≥ 750 mm	4	<b>Core board</b> Highly compressed core board		
<b>Resistance to staining</b> EN 438	Group 1 + 2: grade 5 Group 3: grade 4	5	<b>Profile connection</b> Fold-Down (5G)		
<b>Swelling value</b> ISO 24336	≤ 18 %	6	<b>Backing</b> Melamine resin		
<b>Residual indentation</b> EN ISO 24343-1	Residual indentation ≤ 0.05 mm	<b>Underlay mats:</b> CS-Wert requirement ≥ 120 kPa wineo PERFECT FIT recommendation: <b>soundPROTECT or soundPROTECT Profi</b> (separately available)			
<b>Effect of a furniture leg</b> EN 424	Foot type 0 – no visible change				
<b>Thermal resistance</b> EN 12667	0.0587 (m <sup>2</sup> K)/W				
<b>Castor chair test</b> EN 425	25000 revolutions no damage with rolls type W				
<b>Light fastness</b> EN ISO 105-B02	Light fastness (method 2) ≥ 4				
<b>REACH</b>	free from SVHC-substances ≥ 0.1 %	 <a href="http://www.blauer-engel.de/uz176">www.blauer-engel.de/uz176</a>			
<b>Disposal</b>	<u>Private:</u> like laminated furniture; possible with normal domestic refuse <u>Commercial:</u> Refuse-key-no. AVV 170201				
Windmüller GmbH Nord-West-Ring 21 D-32832 Augustdorf  DOP: 0101011 EN 14041:2004 / AC2006 0766   www.wineo.de		 Information representative des émissions dans l'air intérieur des substances volatiles présentant un risque de toxicité par inhalation, sur une échelle de classe allant de C (fortes émissions) à A+ (très faibles émissions)			
<b>Relevant Information:</b> <ul style="list-style-type: none"> <li>Underfloor heating: In conjunction with suitable underlay material (soundPROTECT or equivalent) suitable for all conventional hot water underfloor heating and electrical systems regulated up to a surface temperature of 27° C.</li> <li>Cleaning and care: see separate cleaning &amp; care instruction.</li> <li>Technical subjects can be changed by Windmüller GmbH.</li> </ul>					