























TECHNICAL CHARACTERISTICS

PURLINE living to glue
 Permanently elastic polyurethane flooring according to EN 16776
 Without the addition of chlorin, without plasticisers or solvents.

wineo

	wood L		
Format	1200 x 200 mm		
Product thickness	2.2 mm		
Weight	3.0 kg/m ²		
Planks / m² per box	23 / 5.52 m ²		
Boxes / m² per pallet	60 / 331.20 m ²		

Guarantee You can find our guarantee conditions at – www.wineo.de

Classification		Product composition	
	Utilization class 23 EN ISO 10874	Domestic area with intensive usage	1 Top element <ul style="list-style-type: none"> • PU-top layer with surface structure • decor paper • stabilisation
	Utilization class 31 EN ISO 10874	Commercial sector with low or occasional usage	
	Scratch resistance EN 16776, annex A	Utilization class 23: > 3 N Utilization class 31: > 5 N	
	R9 Anti slip category DIN 51130	R 9	2 Base layer high performance composite material
	Staining and chemical resistance EN ISO 26987	Very good resistance according to the concentration and residence time	3 Backing Integrated Fleece TEC System
	Light fastness EN ISO 105-B02	≤ 6	
	Residual indentation EN ISO 24343-1	≤ 0.10 mm	
	Effect of a furniture leg EN 424	Utilization class 23: Foot type 3 Utilization class 31: Foot type 3 no visible change	       
	Castor chair test EN 425	25000 revolutions no damage with rolls type W	
	Thermal resistance ISO 8302	0.01 (m ² K)/W	
	Impact sound reduction EN ISO 10140	~ 8 dB ~ 17 dB in the system with silentPLUS	
	Dimension stability EN ISO 23999	≤ 0.15 %	
	Flexural behaviour EN ISO 24344	≥ 20 mm	
	REACH	free from SVHC substances ≥ 0.1 %	
	Disposal	<u>Private:</u> possible with normal domestic refuse <u>Commercial:</u> Refuse-key-no. AVV 170203	

CE
- 25 -

Windmüller GmbH
Charles-Lindbergh-Ring 13
D-32756 Detmold

DOP: 2001010
EN 14041:2004 / AC2006
1658

www.wineo.de

ÉMISSIONS DANS L'AIR INTÉRIEUR

A+

A+ A B C

Information representative des émissions dans l'air intérieur des substances volatiles présentant un risque de toxicité par inhalation, sur une échelle de classe allant de C (fortes émissions) à A+ (très faibles émissions)

DGNB NAVIGATOR

Registrierungs-Code
NAPCCU

www.dgnb-navigator.de

Relevant Information:

- Underfloor heating: Suitable for all conventional hot water underfloor heating and electrical systems regulated up to a surface temperatur of 29 °C.
- Cleaning and care: See separate cleaning & care instruction.
- Technical subjects can be changed by Windmüller GmbH.