






























TECHNICAL CHARACTERISTICS

PURLINE organic flooring | wineo 1000 G'16 to glue

Permanently elastic polyurethane flooring according to EN 16776
Without the addition of chlorin, without plasticisers or solvents.

wineo

 to glue	wineo 1000 wood	wineo 1000 stone	
Format	1298 x 200 mm	862 x 402 mm	
Product thickness	2.2 mm	2.2 mm	
Weight	3.0 kg/m ²	3.0 kg/m ²	
Planks / m² per box	20 / 5.19 m ²	14 / 4.86 m ²	
Boxes / m² per pallet	48 / 249.12 m ²	50 / 243 m ²	
Guarantee	30 years – Guarantee for private use according to Windmüller warranty conditions – www.wineo.de		
Classification		Product composition	
 Utilization class 23 EN ISO 10874	Domestic area with intensive usage		1
 Utilization class 32 EN ISO 10874	Commercial sector with average usage		
Scratch resistance EN 16776, annex A	Utilization class 23: > 3 N Utilization class 32: > 5 N		
 R9 Anti slip category DIN 51130	R 9		2
 Staining and chemical resistance EN ISO 26987	Very good resistance according to the concentration and residence time		
 Light fastness EN ISO 105-B02	~ 7		3
 Residual indentation EN ISO 24343-1	≤ 0.10 mm		
 Effect of a furniture leg EN 424	Utilization class 23: Foot type 3 Utilization class 32: Foot type 2 no visible change		
 Castor chair test EN 425	25000 revolutions no damage with rolls type W		
 Thermal resistance ISO 8302	0.01 (m ² K)/W		
 Impact sound reduction EN ISO 10140	~ 4 dB ~ 17 dB in the system with silentPLUS		
 Dimension stability EN ISO 23999	≤ 0.15 %		
 Flexural behaviour EN ISO 24344	≥ 20 mm		
REACH	free from SVHC substances ≥ 0.1 %		
Disposal	<u>Private:</u> possible with normal domestic refuse <u>Commercial:</u> Refuse-key-no. AVV 170203		
 Windmüller GmbH Nord-West-Ring 21 D-32832 Augustdorf DOP: 2001010 EN 14041:2004 / AC2006 1658      www.wineo.de		 ÉMISSIONS DANS L'AIR INTÉRIEUR A+ Information representative des émissions dans l'air intérieur des substances volatiles présentant un risque de toxicité par inhalation, sur une échelle de classe allant de C (fortes émissions) à A+ (très faibles émissions)	
 DGNB NAVIGATOR Registrierungs-Code NAPCCU www.dgnb-navigator.de		 GREENGUARD GREENGUARD GOLD	
 floor score CERTIFIED BY SCS Global Services		 BLAUER ENGEL DAS UMWELTZEICHEN www.blauer-engel.de/uz120	
 Bewertung eco 2 eco-bau		 THE INDOOR CLIMATE LABEL	
 EPD THIRD-PARTY VERIFIED Institut Bauen und Umwelt e.V.		 EMISSION CLASS FOR BUILDING MATERIAL M1	

Relevant Information:

- Underfloor heating: Suitable for all conventional hot water underfloor heating and electrical systems regulated up to a surface temperatur of 27 °C.
- Cleaning and care: See separate cleaning & care instruction.
- Technical subjects can be changed by Windmüller GmbH.