





TECHNICAL CHARACTERISTICS











PURLINE organic flooring | wineo 1000 Multi-Layer to click

Long-lasting multi-layer flooring according to ISO 20326 for glueless installation

wineo

|  | wood L | wood XL | stone L |
|---|--|---|---|
| Format | 1288 x 187 mm | 1520 x 238 mm | 636 x 319 mm |
| Product thickness | 9 mm | 9 mm | 9 mm |
| Weight | 8.70 kg/m ² | 8.70 kg/m ² | 8.70 kg/m ² |
| Profile connection | Fold-Down  | Fold-Down  | LocTec  |
| Planks / m² per box | 8 / 1.93 m ² | 6 / 2.17 m ² | 9 / 1.83 m ² |
| Boxes / m² per pallet | 44 / 84.92 m ² | 48 / 104.16 m ² | 60 / 109.80 m ² |
| Guarantee | Life Time Guarantee for private use according to Windmüller warranty conditions – www.wineo.de | | |



| Classification | | Product composition |
|--|---|---|
|  Utilization class 23 EN ISO 10874 | Domestic area with intensive usage | 1 Top element • PU-top layer with surface-structure • decor paper • stabilisation |
|  Utilization class 32 EN ISO 10874 | Commercial sector with average usage | |
|  R9 Anti slip category DIN 51130 | R 9 | |
|  Staining and chemical resistance EN ISO 26987 | Very good resistance according to the concentration and residence time | 2 Profile connection Fold-Down locking (wood) LocTec locking (stone) |
|  Light fastness EN ISO 105-B02 | ~ 7 | 3 Core board Swell-protected Aqua-Protect® HDF core board |
|  Residual indentation EN ISO 24343-1 | ~ 0.05 mm | 4 Underlay Integrated underlay soundPROTECT |
|  Castor chair test EN 425 | 25000 revolutions no damage with rolls type W | |
|  Thermal resistance EN 12667 | 0.06 (m ² K)W | |
|  Sound-Protect Eco Impact sound reduction EN ISO 10140 | ~ 15 dB |  www.blauer-engel.de/uz176 |
| Reflected walking sound reduction | ~ 29 % | |
| REACH | free from SVHC substances ≥ 0.1 % | |
| Disposal | <u>Private:</u> possible with normal domestic refuse <u>Commercial:</u> Refuse-key-no. AVV 170203 | |

CE - 21 -


Windmüller GmbH
Nord-West-Ring 21
D-32832 Augustdorf

DOP: 2001011
EN 14041:2004 / AC2006
1658



www.wineo.de

ÉMISSIONS DANS L'AIR INTÉRIEUR

 **A+**

A+ A B C

Information representative des émissions dans l'air intérieur des substances volatiles présentant un risque de toxicité par inhalation, sur une échelle de classe allant de C (fortes émissions) à A+ (tres faibles émissions)

TÜV PROFIT CERT
70 710 4061-5
www.profit.com

TFI emissionsgeprüft
schadstoffgeprüft
PREMIUM

Relevant Information:

- Underfloor heating: Suitable for all conventional hot water underfloor heating and electrical systems regulated up to a surface temperatur of 27 °C.
- Cleaning and care: See separate cleaning & care instruction.
- Technical subjects can be changed by Windmüller GmbH.