















TECHNICAL CHARACTERISTICS

PURLINE ORGANIC FLOORING | wineo 1000 to glue

Permanently elastic polyurethane flooring according to EN 16776
free of chlorine, solvents and plasticizers

wineo

 to glue	wineo 1000 wood	wineo 1000 stone	
Format	1298 x 200 mm	862 x 402 mm	
Product thickness	2.2 mm	2.2 mm	
Weight	3.4 kg/m ²	3.4 kg/m ²	
Planks / m² per box	20 / 5.19 m ²	14 / 4.86 m ²	
Boxes / m² per pallet	48 / 249.12 m ²	50 / 243 m ²	
Guarantee	10 years – Guarantee for private use according to Windmüller warranty conditions – www.wineo.de		

Classification		Product composition
 Utilization class 23 EN ISO 10874	Heavy-duty use in the domestic area	1 Top element <ul style="list-style-type: none"> • PU-top layer with surface structure • decor paper • stabilisation with ecuran
 Utilization class 32 EN ISO 10874	Normal use in the commercial sector	
 R9 Anti slip category DIN 51130	R 9	
 Staining and chemical resistance EN ISO 26987	Very good resistance according to the concentration and residence time	2 Base layer ecuran high performance composite material
 Light fastness EN ISO 105-B02	~ 7	
 Residual indentation EN ISO 24343-1	~ 0.05 mm	3 Backing Integrated Fleece TEC System
 Effect of a furniture leg EN 424	Foot type 0 – no visible change	
 Castor chair test EN 425	25000 revolutions no damage with rolls type W	
 Thermal resistance ISO 8302	0.01 (m ² K)/W	
 Impact sound reduction EN ISO 10140	~ 4 dB	
 Dimension stability EN ISO 23999	~ 0.10 %	
 Flexural behaviour EN ISO 24344	< 20 mm	
Disposal	<u>Private:</u> possible with normal domestic refuse <u>Commercial:</u> Refuse-key-no. AVV 170203	




www.blauer-engel.de/uz120















Windmüller GmbH
Nord-West-Ring 21
D-32832 Augustdorf

DOP: 2001010
EN 14041:2004 / AC2006
1658

www.wineo.de

ÉMISSIONS DANS L'AIR INTÉRIEUR



Information representative des émissions dans l'air intérieur des substances volatiles présentant un risque de toxicité par inhalation, sur une échelle de classe allant de C (fortes émissions) à A+ (très faibles émissions)

DGNB NAVIGATOR

Registrierungs-Code
NAPCCU

www.dgnb-navigator.de

Relevant Information:

- Underfloor heating: Suitable for all conventional hot water underfloor heating and electrical systems regulated up to a surface temperatur of 27 °C.
- Cleaning and care: See separate cleaning & care instruction.
- Technical subjects can be changed by Windmüller GmbH.