


















PURLINE organic flooring | wineo 1000 G'16 wood XXL Multi-Layer to click

wineo

Long-lasting multi-layer flooring according to ISO 20326 for glueless installation

	wineo 1000 wood XXL Multi-Layer to click			
Format	1845 x 237 mm			
Product thickness	9 mm			
Weight	8.70 kg/m ²			
Planks / m² per box	5 / 2.19 m ²			
Boxes / m² per pallet	48 / 105.12 m ²			
Guarantee	30 years – Guarantee for private use according to Windmüller warranty conditions – www.wineo.de			
Classification			Product composition	
	Utilization class 23 EN ISO 10874	Heavy-duty use in the domestic area	1	Top element <ul style="list-style-type: none"> • PU-top layer with surface-structure • decor paper • stabilisation
	Utilization class 32 EN ISO 10874	Normal use in the commercial sector		
	R9 Anti slip category DIN 51130	R 9		
	Staining and chemical resistance EN ISO 26987	Very good resistance according to the concentration and residence time	2	Profile connection Fold-Down locking 
	Light fastness EN ISO 105-B02	~ 7	3	Core board Swell-protected Aqua-Protect® HDF core board
	Residual indentation EN ISO 24343-1	~ 0.05 mm	4	Underlay Integrated underlay soundPROTECT
	Castor chair test EN 425	25000 revolutions no damage with rolls type W		
	Thermal resistance EN 12667	0.06 (m ² K)W	 www.blauer-engel.de/uz176	
	Impact sound reduction EN ISO 10140	~ 15 dB		
	Reflected walking sound reduction	~ 29 %		
	REACH	free from SVHC substances ≥ 0.1 %		
	Disposal	<u>Private:</u> possible with normal domestic refuse <u>Commercial:</u> Refuse-key-no. AVV 170203		
 Windmüller GmbH Nord-West-Ring 21 D-32832 Augustdorf DOP: 2001011 EN 14041:2004 / AC2006 1658  www.wineo.de			 Information representative des émissions dans l'air intérieur des substances volatiles présentant un risque de toxicité par inhalation, sur une échelle de classe allant de C (fortes émissions) à A+ (tres faibles émissions)	
			 TÜV PROFIT CERT 70 710 4061-5 www.profitcert.com emissionsgeprüft schadstoffgeprüft PREMIUM	

Relevant Information:

- Underfloor heating: Suitable for all conventional hot water underfloor heating and electrical systems regulated up to a surface temperatur of 27 °C.
- Cleaning and care: See separate cleaning & care instruction.
- Technical subjects can be changed by Windmüller GmbH.