























TECHNICAL CHARACTERISTICS

PURLINE organic flooring | wineo 1000 G'16 to click

Permanently elastic polyurethane flooring according to EN 16776
free of chlorine, solvents and plasticizers

wineo






 to click	wineo 1000 wood	wineo 1000 stone	
Format	1295 x 195 mm	859 x 397 mm	
Product thickness	5 mm	5 mm	
Weight	9 kg/m ²	9 kg/m ²	
Planks / m² per box	8 / 2.02 m ²	6 / 2.05 m ²	
Boxes / m² per pallet	48 / 96.96 m ²	48 / 98.40 m ²	
Guarantee	30 years – Guarantee for private use according to Windmüller warranty conditions – www.wineo.de		

Classification		Product composition		
 Utilization class 23 EN ISO 10874	Heavy-duty use in the domestic area	1	Top element <ul style="list-style-type: none"> • PU-top layer with surface structure • decor paper • stabilisation 	
 Utilization class 32 EN ISO 10874	Normal use in the commercial sector			
 R9 Anti slip category DIN 51130	R 9			
 Staining and chemical resistance EN ISO 26987	Very good resistance according to the concentration and residence time	2	Profile connection Connect technology 	
 Light fastness EN ISO 105-B02	~ 7	3		Base layer ecuran high performance composite material
 Residual indentation EN ISO 24343-1	~ 0.05 mm			
 Effect of a furniture leg EN 424	Foot type 0 – no visible change	4		Backing Integrated Fleece TEC-System
 Castor chair test EN 425	25000 revolutions no damage with rolls type W	   <p>www.blauer-engel.de/uz120</p>     		
 Thermal resistance ISO 8302	0.01 (m ² K)/W			
 Impact sound reduction EN ISO 10140	~ 6 dB ~ 16 dB in the system with silentCOMFORT			
 Dimension stability EN ISO 23999	~ 0.10 %			
REACH	free from SVHC substances ≥ 0.1 %			
Disposal	<u>Private:</u> possible with normal domestic refuse <u>Commercial:</u> Refuse-key-no. AVV 170203			

CE Windmüller GmbH
Nord-West-Ring 21
D-32832 Augustdorf

DOP: 2001010
EN 14041:2004 / AC2006
1658

- 18 -

www.wineo.de

EMISSIONS DANS L'AIR INTÉRIEUR

A+

A+ A B C

Information representative des émissions dans l'air intérieur des substances volatiles présentant un risque de toxicité par inhalation, sur une échelle de classe allant de C (fortes émissions) à A+ (très faibles émissions)


DGNB NAVIGATOR

Registrierungs-Code
NAPCCU
www.dgnb-navigator.de

GREENGUARD

PRODUCT CERTIFIED FOR LOW VOC EMISSIONS IN INTERIORS

GOLD



floor score

CERTIFIED BY
SCS Global Services

THIRD-PARTY VERIFIED
EPD
Institut Bauen und Umwelt e.V.

Bewertung
basis
eco-bau

THE INDOOR CLIMATE LABEL

EMISSION CLASS FOR BUILDING MATERIAL
M1

Relevant Information:

- Underfloor heating: Suitable for all conventional hot water underfloor heating and electrical systems regulated up to a surface temperatur of 27 °C.
- Cleaning and care: See separate cleaning & care instruction.
- Technical subjects can be changed by Windmüller GmbH.