

TECHNICAL CHARACTERISTICS

PURLINE organic flooring | wineo 1200 to click (Semi-Rigid)


Permanently elastic polyurethane flooring according to EN 16776
Without the addition of chlorin, without plasticisers or solvents.

wineo

	wineo 1200 wood XL V4	wineo 1200 stone XL
Format	1507 x 246 mm	1000 x 500 mm
Product thickness	5 mm	5 mm
Weight	9 kg/m²	9 kg/m²
Profile connection	Fold-Down 	LocTec 
Planks / m² per box	6 / 2.22 m²	6 / 3.00 m²
Boxes / m² per pallet	48 / 106.56 m²	36 / 108.00 m²
Guarantee	30 years – Guarantee for private use according to Windmüller warranty conditions – www.wineo.de	



Classification			Product composition
	Utilization class 23 EN ISO 10874	Domestic area with intensive usage	1 Top element • PU-top layer with surface structure • decor paper • stabilisation
	Utilization class 33 EN ISO 10874	Commercial sector with heavy usage	
	Scratch resistance EN 16776, annex A	Utilization class 33: ≥ 6 N	
	R9 Anti slip category DIN 51130	R 9	2 Profile connection wood XL – Fold-Down stone XL – LocTec
	Staining and chemical resistance EN ISO 26987	Very good resistance according to the concentration and residence time	
	Light fastness EN ISO 105-B02	~ 7	3 Base layer ecuran high performance composite material Tele-Stop feature 
	Residual indentation EN ISO 24343-1	≤ 0.10 mm	
	Effect of a furniture leg EN 424	in test: Foot type 2 – no visible change	4 Backing Integrated Fleece TEC-System
	Castor chair test EN ISO 4918	25000 revolutions no damage with rolls type W	
	Thermal resistance ISO 8302	0.01 (m ² K)/W	wood XL  V4 joint lacquered
	Impact sound reduction EN ISO 10140	in test	
	Dimension stability EN ISO 23999	≤ 0.15 %	 SILVER  PREMIUM  www.blauer-engel.de/uz120
REACH		free from SVHC substances ≥ 0.1 %	
Disposal		<u>Private:</u> possible with normal domestic refuse <u>Commercial:</u> Refuse-key-no. AVV 170203	



Relevant Information:

- Underfloor heating: Suitable for all conventional hot water underfloor heating and electrical systems regulated up to a surface temperatur of 27 °C.
- Cleaning and care: See separate cleaning & care instruction.
- Technical subjects can be changed by Windmüller GmbH.