
































TECHNICAL CHARACTERISTICS

PURLINE organic flooring wineo 1500 safety roll to glue Permanently elastic polyurethane flooring according to EN 16776 with structured, anti-slip surface in R10 according to DIN 51130 free of chlorine, solvents and plasticizers			
Format 	20 x 2 m		
Product thickness	2.5 mm		
Weight	3.6 kg/m ²		
Roll / m²	1 / 40 m ²		
Rolls / m² per pallet	6 / 240 m ²		
Classification		Product composition	
 Utilization class 23 EN ISO 10874	Heavy-duty use in the domestic area	1	Top element <ul style="list-style-type: none"> • PU-top layer with surface structure R10 • decor paper • stabilisation
 Utilization class 34 EN ISO 10874	Very heavy-duty use in the commercial sector		
 Utilization class 43 EN ISO 10874	Heavy-duty use in the light industrial sector		
Decontamination DIN 25415	Easy to decontaminate	2	Base layer ecuran high performance composite material
Anti slip category For wet barefoot areas - DIN 51097	A/B		
 R10 Anti slip category DIN 51130	R 10	3	Backing Integrated Fleece TEC-System
 Staining and chemical resistance EN ISO 26987	Very good resistance according to the concentration and residence time	   <p>www.blauer-engel.de/uz120</p>    	
 Light fastness EN ISO 105-B02	~ 7		
 Residual indentation EN ISO 24343-1	~ 0.05 mm		
 Effect of a furniture leg EN 424	Foot type 0 – no visible change		
 Castor chair test EN 425	25000 revolutions no damage with rolls type W		
 Thermal resistance ISO 8302	~ 0.01 (m ² K)/W		
 Impact sound reduction EN ISO 10140	~ 4 dB		
 Dimension stability EN ISO 23999	~ 0.05 %		
 Flexural behaviour EN ISO 24344	≥ 20 mm		
REACH	free from SVHC substances ≥ 0.1 %		
Disposal	<u>Private:</u> possible with normal domestic refuse <u>Commercial:</u> Refuse-key-no. AVV 170203		
 Windmüller GmbH Nord-West-Ring 21 D-32832 Augustdorf DOP: 2301010 EN 14041:2004 / AC2006 1658     www.wineo.de		 ÉMISSIONS DANS L'AIR INTÉRIEUR A+ A B C Information representative des émissions dans l'air intérieur des substances volatiles présentant un risque de toxicité par inhalation, sur une échelle de classe allant de C (fortes émissions) à A+ (tres faibles émissions)	
 DGNB NAVIGATOR Registrations-Code NAPCCU www.dgnb-navigato.de		 GREENGUARD GREENGUARD CERTIFIED GREENGUARD GOLD THIRD-PARTY VERIFIED EPD Institut Bauen und Umwelt e.V.	

Relevant Information:

- Underfloor heating: Suitable for all conventional hot water underfloor heating and electrical systems regulated up to a surface temperatur of 27 °C.
- Cleaning and care: See separate cleaning & care instruction.
- Technical subjects can be changed by Windmüller GmbH.