


TECHNICAL CHARACTERISTICS






















PURLINE ORGANIC FLOORING wineo 1500 safety | roll to glue

Permanently elastic polyurethane flooring according to EN 16776 with structured, anti-slip surface in R10 according to DIN 51130 free of chlorine, solvents and plasticizers

wineo

Format 	20 x 2 m
Product thickness	2.5 mm
Weight	3.6 kg/m ²
Roll / m²	1 / 40 m ²
Rolls / m² per pallet	6 / 240 m ²







Classification		Product composition
 Utilization class 23 EN ISO 10874	Heavy-duty use in the domestic area	1 Top element • PU-top layer with surface structure • decor paper • stabilisation with ecuran
 Utilization class 34 EN ISO 10874	Very heavy-duty use in the commercial sector	
 Utilization class 43 EN ISO 10874	Heavy-duty use in the light industrial sector	
Decontamination DIN 25415	Easy to decontaminate	2 Base layer ecuran high performance composite material
Anti slip category For wet barefoot areas - DIN 51097	A/B	
 R10 Anti slip category DIN 51130	R 10	3 Backing Integrated Fleece TEC-System
 Staining and chemical resistance EN ISO 26987	Very good resistance according to the concentration and residence time	 www.blauer-engel.de/uz120       
 Light fastness EN ISO 105-B02	~ 7	
 Residual indentation EN ISO 24343-1	~ 0.05 mm	
 Effect of a furniture leg EN 424	Foot type 0 – no visible change	
 Castor chair test EN 425	25000 revolutions no damage with rolls type W	
 Thermal resistance ISO 8302	~ 0.01 (m ² K)/W	
 Impact sound reduction EN ISO 10140	~ 4 dB	
 Dimension stability EN ISO 23999	~ 0.05 %	
 Flexural behaviour EN ISO 24344	< 20 mm	
Disposal	<u>Private:</u> possible with normal domestic refuse <u>Commercial:</u> Refuse-key-no. AVV 170203	

CE - 18 -

Windmüller GmbH
Nord-West-Ring 21
D-32832 Augustdorf

DOP: 2301010
EN 14041:2004 / AC2006
1658

www.wineo.de

ÉMISSIONS DANS L'AIR INTÉRIEUR

A+

A+ A B C

Information representative des émissions dans l'air intérieur des substances volatiles présentant un risque de toxicité par inhalation, sur une échelle de classe allant de C (fortes émissions) à A+ (tres faibles émissions)

DGNB NAVIGATOR

Registrations-Code
NAPCCU
www.dgnb-navigator.de

GREENGUARD

PRODUCT CERTIFIED FOR LOW VOC EMISSIONS IN USE

GOLD

floor score

CREATED BY SCS Global Services

THE INDOOR CLIMATE LABEL

THIRD-PARTY VERIFIED EPD

Institut Bauen und Umwelt e.V.

Relevant Information:

- Underfloor heating: Suitable for all conventional hot water underfloor heating and electrical systems regulated up to a surface temperatur of 27 °C.
- Cleaning and care: See separate cleaning & care instruction.
- Technical subjects can be changed by Windmüller GmbH.