


TECHNICAL CHARACTERISTICS

PURLINE organic flooring | wineo 1500 sea

Permanently elastic polyurethane flooring according to EN 16776

Free of chlorine, solvents and plasticizers.

wineo

 or 	wood 	wood XL 	stone 	stone XL 	roll 	
Format	1200 x 200 mm	1500 x 250 mm	670 x 335 mm	1000 x 500 mm	20 x 2 m	
Product thickness	2.5 mm	2.5 mm	2.5 mm	2.5 mm	2.5 mm	
Weight / Plank/roll	3.6 kg/m²	3.6 kg/m²	3.6 kg/m²	3.6 kg/m²	3.6 kg/m²	
Classification						Product composition
	Utilization class 23 EN ISO 10874		Domestic area with intensive usage			1 Top element • PU-top layer with surface structure • decor paper • stabilisation
	Utilization class 34 EN ISO 10874		Commercial sector with intensive usage			
	Utilization class 43 EN ISO 10874		Light industry sector with heavy usage			
	R9 Anti slip category DIN 51130		R 9			2 Base layer ecuran high-performance composite material
	Slip resistance EN 13893		μ ≥ 0.30 – DS			
	Anti-static properties EN 1815		≤ 2 kV			3 Backing integrated FleeceTEC-System
	Staining and chemical resistance EN ISO 26987		Resistant (detailed list available on request)			
	Light fastness EN ISO 105-B02		~ 7			
	Residual indentation EN ISO 24343-1		~ 0.05 mm			
	Effect of a furniture leg EN 424		Foot type 0 – no visible change			
	Castor chair test EN 425		25000 revolutions no damage with rolls type W			
	Thermal resistance ISO 8302		~ 0.01 (m²K)/W			
	Impact sound reduction EN ISO 10140		~ 4 dB			
	Dimension stability EN ISO 23999		≤ 0.10 %			
	Flexural behaviour EN ISO 24344		~ 20 mm			
REACH			free from SVHC substances ≥ 0.1 %			
Fire test – Inland and maritime shipping MSC.307 (88) – IMO 2010 FTP Code Part 5			passed			 0045 2021
Evaluation of the flue gas – Inland and maritime shipping MSC.307 (88) – IMO 2010 FTP Code Part 2			passed			
MED / 3.18c according to 2014/90/EU in conjunction with the respective valid implementing regulation. Module B - wineo 1500 sea U.S. Coast Guard Approval No.: Module D - Windmüller GmbH U.S. Coast Guard No.:			Certificate No. M18008 164.117/EC0045 Certificate No. M18004 164.117/EC0045/M18004			

Relevant Information:

- Underfloor heating: Suitable for all conventional hot water underfloor heating and electrical systems regulated up to a surface temperature of 27 °C.
- Cleaning and care: See separate cleaning & care instruction.
- Technical subjects can be changed by Windmüller GmbH.