TECHNICAL CHARACTERISTICS

PURLINE | wineo 1000 Multi-Layer to click

Long-lasting multi-layer flooring according to ISO 20326 for glueless installation

wineo

	wood L	wood XL	stone L
Format	1288 x 187 mm	1520 x 238 mm	636 x 319 mm
Product thickness	9 mm	9 mm	9 mm
Weight	8.70 kg/m²	8.70 kg/m²	8.70 kg/m²
Profile connection	Fold-Down	Fold-Down	LocTec
Planks / m² per box	8 / 1.93 m²	6 / 2.17 m²	9 / 1.83 m²
Boxes / m² per pallet	44 / 84.92 m²	48 / 104.16 m²	60 / 109.80 m²
Guarantee	You can find our guarantee conditions at – www.wineo.de		



Classification

Utilization class 23 EN ISO 10874	Domestic area with intensive usage
Utilization class 32 EN ISO 10874	Commercial sector with average usage
Anti slip category DIN 51130	R 9
Staining and chemical resistance EN ISO 26987	Very good resistance according to the concentration and residence time
Light fastness EN ISO 105-B02	~ 7
Residual indentation EN ISO 24343-1	~ 0.05 mm
Castor chair test EN 425	25000 revolutions no damage with rolls type W
Thermal resistance EN 12667	0.06 (m²K)W
Impact sound reduction EN ISO 10140	~ 15 dB
Reflected walking sound reduction	~ 29 %
REACH	free from SVHC substances ≥ 0.1 %
Disposal	Private: possible with normal domestic refuse Commercial: Refuse-key-no. AVV 170203

Product composition

1	**Top element** • PU-top layer with surface-structure • decor paper • stabilisation
2	**Profile connection** Fold-Down locking (wood) LocTec locking (stone)
3	**Core board** Swell-protected Aqua-Protect® HDF core board
4	**Underlay** Integrated underlay soundPROTECT

CE
Windmöller GmbH
Charles-Lindbergh-Ring 13
D-32756 Detmold
- 25 -
DOP: 2001011
EN 14041:2004 / AC2006
1658
C_{fl}-s1 | DS | E1 HCHO | ≤ 2 kV | ≥ 0,07 W/(mK)
www.wineo.de

ÉMISSIONS DANS L'AIR INTÉRIEUR
A+ A B C
Information representative des emissions dans l'air interieur des substances volatiles presentant un risque de toxicite par inhalation, sur une echelle de classe allant de C (fortes emissions) a A+ (tres faibles emissions)

full scope CERTIFIED cradle to cradle bronze version 4.1 C2CCERTIFIED.ORG

BLAUER ENGEL DAS UMWELTZEICHEN
www.blauer-engel.de/uz176

TÜV PROFI CERT product 70 710 4061-5
emissionsgeprüft schadstoffgeprüft PREMIUM

Relevant Information:

- Underfloor heating: Suitable for all conventional hot water underfloor heating and electrical systems regulated up to a surface temperatur of 27 °C.
- Cleaning and care: See separate cleaning & care instruction.
- Technical subjects can be changed by Windmöller GmbH.