wineo

ACCESSORIES

Wineo



Underlay

Skirting

Skirting External Weld rods

Installatio

FLOORING

CONTENT

material	04
boards	12
boards corners Inside corners	
s	22
on tools	24

UNDERLAY MATERIAL PRODUCT FINDER

FOR PURLINE® ORGANIC FLOORING & DESIGN FLOORING

Installation of	Installation type	Installation	Special feature	Product
wineo	for gluing	floating	self-adhesive on one side	singleGLUE
PURLINE® organic flooring		glued	self-adhesive on both sides	doubleGLUE
or			combined with liquid glue	silentPLUS
design flooring and comparable	for clicking in	floating	for elastic click-floors	silentCOMFORT
design floors for gluing and clicking in			Rigid-click < 4 mm	silentRIGID COMPACT
grang and bloking in			(Semi-) Rigid-click	silentRIGID

PU SELF-ADHESIVE MATS

FOR PURLINE® ORGANIC FLOORING & DESIGN FLOORING

singleGLUE | Art.-Nr. KPU1020



THE INNOVATIVE SOLUTION FOR THE FLOATING INSTALLATION OF ELASTIC FLOOR COVERINGS FOR GLUING, WITHOUT LIQUID ADHESIVE

- floating installation of plank and sheet material
- self-adhesive top surface, floating installation, ultra-fast
- perfect solution for underfloor heating

Fits to PURLINE® organic flooring & design flooring for gluing: wineo 400 | 600 | 800 |1000 | 1200 | 1500

and all comparable elastic dryback floor coverings

The singleGLUE is an underlay with a self-adhesive top surface. The underlay is rolled out in a floating arrangement, i.e. loose on the screed. Once the protective film has been removed, the flooring can be glued on top and is then fixed using a roller. Working without liquid adhesive is extremely clean and installation is very quick. Surfaces can be walked on immediately and thanks to the floating installation the flooring can be removed without leaving any residue.

Technical characteristics

Base material:	ecuran (bio-polyurethane)
Rolls/pallets:	40
Roll:	6.5 m ²
Thickness:	1.8 mm
Width:	1 m
Length:	6.5 m
Weight:	2.6 kg / m²
Impact sound reduction:	~ 15 dB
Thermal resistance:	0.01 (m²K)/W

UNDERLAY MATERIAL PRODUCT FINDER

FOR LAMINATE FLOORING & PARQUET FLOORING

Installation of	Anforderung	Substrate	Product
laminate flooring	Underfloor heating	mineral based	soundPROTECT SD
or parquet flooring			soundPROTECT PROFI SD
purquot nooring		non-mineral based	soundPROTECT
			soundPROTECT PROFI
	Heat insulation	mineral based	insulationBOARD + PE vapour barrier
		non-mineral based	insulationBOARD







doubleGLUE | Art.-Nr. KPU1050



THE STRONG SOLUTION FOR A DOUBLE-SIDED ADHESION OF ELASTIC FLOOR COVERINGS FOR GLUING, WITHOUT LIQUID ADHESIVE

- double-sided installation of plank and sheet material
- suitable for the installation of large areas
- no expansion joints
- perfect solution for underfloor heating

Fits to PURLINE® organic flooring & design flooring for gluing: wineo 400 | 600 | 800 |1000 | 1200 | 1500

and all comparable elastic dryback floor coverings

The **doubleGLUE** underlay with a **self-adhesive topand backside**, is additionally **glued** to the substrate. This strong bonding in many cases allows for the **elimination of expansion joints** between rooms and makes an installation of very large areas possible. Also surfaces can be walked on immediately, other trades do not have to wait.

Technical characteristics	
Base material:	ecuran (bio-polyurethane)
Rolls/pallets:	40
Rolle:	6.5 m²
Thickness:	1.8 mm
Width:	1 m
Length:	6.5 m
Weight:	2.6 kg / m²
Impact sound reduction:	~ 13 dB
Thermal resistance:	0.01 (m²K)/W

PU UNDERLAYS

FOR PURLINE[®] ORGANIC FLOORING & DESIGN FLOORING

silentPLUS | Art. no. UPU1020





silentCOMFORT | Art. no. UCT1000



THE PLUS IN QUIETNESS FOR FULL-SURFACE BONDING OF ELASTIC FLOOR COVERINGS FOR GLUING

- self-adhesive below, full-surface bonding above, ultra-quiet
- perfect solution for underfloor heating

■ up to utilisation class 23/33

Fits to PURLINE® organic flooring & design flooring for gluing: wineo 400 | 600 | 800 | 1000 | 1500 and all comparable elastic dryback fl oor coverings

silentPLUS is an underlay with a self-adhesive lower surface. Once the protective film has been removed, the underlay is stuck to the substrate. The flooring is then fitted with an additional adhesive on the entire upper surface. This double adhesive method reduces impact noise up to 17 dB and guarantees that special bonus of very low noise.

Technical characteristics	
Base material:	ecuran (bio-polyurethane)
Rolls/pallets:	40
Roll:	8 m²
Thickness:	2mm
Width:	1 m
Length:	8 m
Weight:	2 kg / m²
Impact sound reduction:	~ 17 dB
Thermal resistance:	0.01 (m²K)/W

THE CONVENIENT MAT FOR STABLE CLICKING INSTALLATION OF ELASTIC FLOOR COVERINGS

- adhesive top surface, floating installation, ultra-stable
- perfect solution for underfloor heating

Fits to PURLINE[®] organic flooring & design flooring for clicking in: wineo 400 | 600 | 800 | 1000 and all comparable elastic dryback floor coverings

silentCOMFORT is the best choice for floating installation of click flooring. The adhesive surface ensures the click connections of the flooring are stable so that the flooring does not slip on the underlay. silentCOMFORT is therefore the most stable underlay for comfortable click installation of elastic flooring.

Technical characteristics	
Base material:	ecuran (bio-polyurethane)
Rolls/pallets:	40
Roll:	10 m ²
Thickness:	1.5 mm
Width:	1 m
Length:	10 m
Weight:	1.5 kg/m²
Impact sound reduction:	~ 16 dB
Thermal resistance:	0.01 (m²K)/W

PU UNDERLAYS

FOR PURLINE® ORGANIC FLOORING & DESIGN FLOORING

silentRIGID COMPACT | Art. no. UPU1050

RECOMMENDED USE FOR THIN RIGID COVERINGS

WITH LESS THAN 4 MM PRODUCT THICKNESS



THE MUST-HAVE FOR THE INSTALLATION OF RIGID-FLOORS FOR CLICKING IN

no breaking of the click connection

- super stabilising
- laid as a floating floor

Fits to thin rigid design flooring for clicking in: with less than 4 mm product thickness

The silentRIGID COMPACT is the perfect underlay for rigid floors with less than 4 mm product thickness. With these types of products it stabilises click connections which are often weak and reduces walking noise.

Technical characteristics	
Base material:	ecuran (bio-polyurethane)
Rolls/pallets:	54
Roll:	10 m²
Thickness:	1.0 mm
Width:	1 m
Length:	10 m
Weight:	1.2 kg/m²
Impact sound reduction:	~ 12 dB
Thermal resistance:	0.01 (m²K)/W







silentRIGID | Art. no. UPU1030

RECOMMENDED USE FOR RIGID COVERINGS



THE MUST-HAVE FOR THE INSTALLATION OF RIGID-FLOORS FOR CLICKING IN

- no breaking of the click connection
- super stabilising
- laid as a floating floor

Fits to (semi-) rigid design flooring for clicking in: wineo 600 l 1200 and any comparable rigid design flooring

The **silentRIGID** was specially developed for **rigid floors in the premium sector**. With these types of products it stabilises click connections which are often weak and reduces walking noise.

Technical characteristics	
Base material:	ecuran (bio-polyurethane)
Rolls/pallets:	54
Roll:	9 m²
Thickness::	1.2 mm
Width:	1 m
Length:	9 m
Weight:	1.5 kg/m²
Impact sound reduction:	~ 13 dB
Thermal resistance:	0.01 (m²K)/W

PU UNDERLAYS

FOR LAMINATE FLOORING & PARQUET FLOORING

oundPROTECT | Art. no. UPU200





soundPROTECT SD | Art. no. UPU200SD





THE ALL-ROUNDER WITH LONG-LIFE PERFORMANCE 2mm

- ultra-quiet, efficient, for a stable click connection
- perfect solution for underfloor heating, suitable for non-mineral subsurfaces (a vapour barrier must be used with mineral subsurfaces)

Fits to all comparable standard laminate and parquet products

soundPROTECT is the perfect 2mm underlay for laminate and parquet flooring. It ensures maximum reduction in impact and reflected walking sound levels, stable retention of the click connection, and is extremely durable.

Technical characteristics	
Base material:	ecuran (bio-polyurethane)
Rolls/pallets:	40
Roll:	8 m²
Thickness:	2 mm
Width:	1 m
Length:	8 m
Weight:	1.7 kg / m²
Impact sound reduction:	~ 19 dB
Reflected walking sound:	~ 28 %
Thermal resistance:	0.01 (m²K)/W

THE ALL-ROUNDER WITH LONG-LIFE PERFORMANCE 2mm

- ultra-quiet, efficient, for a stable click connection
- suitable for mineral subsurfaces (such as screed) thanks to integrated vapour barrier
- perfect solution for underfloor heating

Fits to all comparable standard laminate and parquet products

soundPROTECT SD is the perfect 2mm underlay for laminate and parquet flooring with integrated vapour barrier. It ensures maximum reduction in impact and reflected walking sound levels, stable retention of the click connection, and is extremely durable.

Technical characteristics	
Base material:	ecuran (bio-polyurethane)
Rolls/pallets:	40
Roll:	8 m²
Thickness:	2 mm
Width:	1 m
Length:	8 m
Weight:	1.7 kg/m²
Impact sound reduction:	~ 19 dB
Reflected walking sound:	~ 28 %
Thermal resistance:	0.01 (m²K)/W
SD value:	> 75 m

PU UNDERLAYS FOR LAMINATE FLOORING & PARQUET FLOORING

soundPROTECT PROFI | Art. no. UPU100



THE ALL-ROUNDER FOR PROFESSIONALS WITH LONG-LIFE PERFORMANCE 3mm

ultra-quiet, efficient, for a stable click connection

 perfect solution for underfloor heating, suitable for non-mineral subsurfaces (a vapour barrier must be used with mineral substrates)

Fits to all comparable standard laminate and parquet products

soundPROTECT PROFI is the perfect 3 mm underlay for laminate and parquet flooring. It ensures maximum reduction in impact and reflected walking sound levels, stable retention of the click connection, and is extremely durable.

Technical characteristics	
Base material:	ecuran (bio-polyurethane)
Rolls/pallets:	40
Roll:	5.5 m ²
Thickness:	3 mm
Width:	1 m
Length:	5.5 m
Weight:	2.8 kg / m²
Impact sound reduction:	~ 20 dB
Reflected walking sound:	~ 31 %
Thermal resistance:	0.01 (m²K)/W







soundPROTECT PROFI SD | Art. no. UPU100SD



3mm

- ultra-quiet, efficient, for a stable click connection
- suitable for mineral subsurfaces (such as screed) thanks to integrated vapour barrier
- perfect solution for underfloor heating

Fits to all comparable standard laminate and parquet products

soundPROTECT PROFI SD is the perfect 3 mm underlay for laminate and parquet flooring with integrated vapour barrier. It ensures maximum reduction in impact and reflected walking sound levels, stable retention of the click connection, and is extremely durable.

Technical characteristics	
Base material:	ecuran (bio-polyurethane)
Rolls/pallets:	40
Roll:	5.5 m²
Thickness:	3 mm
Width:	1 m
Length:	5.5 m
Weight:	2.8 kg / m²
Impact sound reduction:	~ 20 dB
Reflected walking sound:	~ 31 %
Thermal resistance:	0.01 (m²K) / W
SD value:	> 75 m





BEST INGREDIENTS FOR BEST RESULTS

The basis of wineo PU underlays and PU self-adhesive mats is ecuran, the unique bio-polyurethane from Windmöller. ecuran is based on plant oils such as canola or castor oil and naturally occurring mineral components such as chalk.



Canola or castor oil

Chalk



PU underlays made of ecuran

- fast, energy-efficient distribution of ground heat
- excellent noise reduction with hard and soft floor coverings
- Iong-life performance of at least 30 years
- excellent residual indentation behaviour
- sustainable raw materials
- without the addition of chlorine, plasticisers or solvents

FOR LAMINATE FLOORING & PARQUET FLOORING

insulationBOARD | Art. no. UHF100



THE STRONG INSULATION BOARD FOR PROFESSIONALS

very good heat insulation, height compensation up to approx. 3 mm, high durability

Fits to all comparable standard laminate and parquet products

insulationBOARD has a proven track record with installation professionals as a **heat insulation underlay**. The insulating board has very good compensation characteristics and is very durable.

Technical characteristics	
Material:	Fibreboard
Boxes/pallets:	26
Quantity/box:	15 pieces (7 m²)
Thickness:	5 mm
Width:	0.59 m
Length:	0.79 m
Weight:	1.28 kg / m²
Impact sound reduction:	~ 19 dB
Reflected walking sound:	11 %
Thermal resistance:	0.071 (m²K) / W

PE FILM & MULTI-PURPOSE SEALING TAPE

FOR LAMINATE FLOORING & PARQUET FLOORING

PE vapour barrier Art. no. UZUB200		
thin PE film for use under all hard flooring (not required for wood substrates)		
 provides a separating layer between screed and underlay materials certified to B2 		
Fits to: soundPROTECT, soundPROT insulationBOARD	ECT PROFI,	
Technical characteristics		
Rolls/pallets:	100	
Roll:	30 m²	
Thickness:	0.125 mm	
Width:	1 m	
Length:	30 m	

Multi-purpose sealing tape | Art. no. UZUB110



- special adhesive tape for sealing the edges of underlay
- required for all underlays with integrated vapour barrier

Fits to:	
soundPROTECT SD, soundPROTECT PROFI SD	

Technical characteristics	
Roll:	1
Width:	38 mm
Length:	20 m





MDF material | Unit = 4



- for the majority of our wineo floorings we offer skirtings similar to the decor, p. 14-22
- for skirtings not listed, we recommend F01CT6



80 x 18 x 2380 mm

MDF material | Unit = 4





MDF material | Unit = 4



MDF material | Unit = 4

$(\mathbf{\hat{n}})$ (www.blauer-engel.de/uz176)

SKIRTING CLIPS



■ invisible skirting board fixings

SKIRTING BOARD ACCESSORIES

ca. 20 rm | box = 50 clips

SKIRTING BOARD ACCESSORIES

INSIDE AND EXTERNAL CORNERS | END CAPS | CONNECTION PIECES



External corners	2	White	FAE01-60
End caps	2	White	FAK01-60
Connection pieces	2	White	FCP01-60



Fits to: Design skirting board			
		T	
Type (self-adhesive)	Unit	Colour	Art. no.
Inside corners	4	White	FIE01-80
External corners	2	White	FAE01-80
End caps	2	White	FAK01-80
Connection pieces	2	White	FCP01-80

FOR PURLINE® ORGANIC FLOORING

wineo 1000

Fits to (Decor art. no.)	16/60 Art. no.
PL308R PLC308R MLP308R	F01CT60 (white)
PL305R PLC305R MLP305R	F6010114
PL307R PLC307R MLP307R	F01CT60 (white)
PL306R PLC306R MLP306R	F6010155
PL298R PLC298R MLP298R	F6010126
PL300R PLC300R MLP300R	F6010131
PL299R PLC299R MLP299R	F6010136
PL296R PLC296R MLP296R	F01CT60 (white)
PL297R PLC297R MLP297R	F01CT60 (white)
PL312R PLC312R MLP312R	F6010116
PL309R PLC309R MLP309R	F6010114
PL311R PLC311R MLP311R	F6010143
PL310R PLC310R MLP310R	F6010124
PL316R PLC316R MLP316R	F6010108
PL314R PLC314R MLP314R	F6010122
PL315R PLC315R MLP315R	F6010116
PL313R PLC313R MLP313R	F01CT60 (white)
PL304R PLC304R MLP304R	F01CT60 (white)
PL295R PLC295R MLP295R	F01CT60 (white)
PL302R PLC302R MLP302R	F01CT60 (white)
PL303R PLC303R MLP303R	F01CT60 (white)
PL301R PLC301R MLP301R	F6010112
	(Decor art. no.) PL308R PLC308R MLP308R PL305R PLC305R MLP305R PL307R PLC307R MLP307R PL306R PLC306R MLP306R PL306R PLC306R MLP306R PL298R PLC298R MLP298R PL300R PLC300R MLP300R PL299R PLC299R MLP299R PL299R PLC299R MLP299R PL296R PLC297R MLP297R PL307R PLC312R MLP312R PL309R PLC309R MLP309R PL312R PLC312R MLP311R PL310R PLC310R MLP310R PL310R PLC316R MLP316R PL316R PLC316R MLP316R PL315R PLC313R MLP315R PL313R PLC313R MLP313R PL314R PLC313R MLP315R PL304R PLC304R MLP304R PL302R PLC302R MLP302R PL302R PLC302R MLP303R



SKIRTING BOARDS

FOR PURLINE® ORGANIC FLOORING

wineo 1200

Design	Fits to (Decor art. no.)	16/60 Art. no.
Announcing Fritz	PL271R PLC271R MLP271R	F6010136
Call me Tilda	PL086R PLC086R MLP086R	F6010121
Cheer for Lisa	PL097R PLC097R MLP097R	F6010153
Hello Martha	PL076R PLC076R MLP076R	F6010101
Let's go Max	PL270R PLC270R MLP270R	F6010118
Say hi to Klara	PL272R PLC272R MLP272R	F6010147
Smile for Emma	PL084R PLC084R MLP084R	F6010105
Welcome Oskar	PL269R PLC269R MLP269R	F6010155



FOR PURLINE® ORGANIC FLOORING

wineo 1500

vineo 1500		
Design	Fits to (Decor art. no.)	16/60 Art. no.
Aspen Oak Dark	PL15000WL	F6010121
Canyon Oak Honey	PL15200WXL	F6010101
Canyon Oak Sand	PL15001WL	F6010120
Crafted Oak	PL15201WXL	F6010101
Durban Oak Brown	PL15002WL	F6010137
Durban Oak Taupe	PL15003WL	F6010138
Fine Oak Brown	PL15202WXL	F6010129
Fine Oak Light	PL15203WXL	F6010134
Fine Oak Nature	PL15204WXL	F6010106
Fjord Maple Beige	PL15205WXL	F01CT60 (white)
Fractal Dark	PL15600GXL	F01CT60 (white)
Fractal Ecru	PL15601GXL	F01CT60 (white)
Fractal Grey	PL15602GXL	F01CT60 (white)
Fractal Light	PL15603GXL	F01CT60 (white)
Fractal Opus	PL15604GXL	F01CT60 (white)
Fractal Wave	PL15605GXL	F01CT60 (white)
Iceland Pine Light	PL15004WL	F6010132
Intensive Oak Amber	PL15206WXL	F6010124
Intensive Oak Brown	PL15207WXL	F6010102
Intensive Oak Nature	PL15208WXL	F6010115
Intensive Oak Taupe	PL15209WXL	F6010104
Lodge Oak Brown	PL15005WL	F6010112
Lodge Oak Dark	PL15006WL	F6010137
Loft Concrete Dark	PL15400SXL	F01CT60 (white)
Loft Concrete Grey	PL15401SXL	F01CT60 (white)
Lugano Walnut Brown	PL15210WXL	F6010108
Mayfield Oak Beige	PL15211WXL	F6010145
Mayfield Oak Brown	PL15212WXL	F6010120
Mayfield Oak Nature	PL15213WXL	F6010124
Mayfield Oak Taupe	PL15214WXL	F6010123
Melbourne Oak Brown	PL15222WXL	F6010108

SKIRTING BOARDS

www.blauer-engel.de/uz176

FOR PURLINE® ORGANIC FLOORING

vineo 1500		
Design	Fits to (Decor art. no.)	16/60 Art. no.
Melbourne Oak Natural	PL15223WXL	F6010149
Metropolitan Marble Dark	PL15402SXL	F01CT60 (white)
Modern Stone Dark	PL15403SXL	F01CT60 (white)
Modern Stone Grey	PL15404SXL	F01CT60 (white)
Newport Oak Brown	PL15007WL	F6010101
Newport Oak Natural	PL15008WL	F6010106
Olevano Marble Grey	PL15405SXL	F01CT60 (white)
Oxford Denim	PL15500TXL	F01CT60 (white)
Oxford Flint	PL15505TXL	F01CT60 (white)
Oxford Ocean	PL15501TXL	F01CT60 (white)
Oxford Oyster	PL15502TXL	F01CT60 (white)
Oxford Slate	PL15503TXL	F01CT60 (white)
Oxford Steel	PL15504TXL	F01CT60 (white)
Portland Concrete Dark	PL15406SXL	F01CT60 (white)
Portland Concrete Grey	PL15407SXL	F01CT60 (white)
Portland Concrete Light	PL15408SXL	F01CT60 (white)
Ravenna Oak Beige	PL15009WL	F6010111
Ravenna Oak Brown	PL15010WL	F6010122
Ravenna Oak Nature	PL15215WXL	F6010122
Real Oak Amber	PL15216WXL	F6010118
Real Oak Nature	PL15217WXL	F6010143
Real Oak Taupe	PL15218WXL	F6010126
Serene Marble Dark	PL15411SXL	F01CT60 (white)
Serene Marble Grey	PL15412SXL	F01CT60 (white)
Serene Marble Light	PL15409SXL	F01CT60 (white)
Serene Marble Nature	PL15410SXL	F01CT60 (white)
Siena Oak Beige	PL15219WXL	F6010145
Siena Oak Brown	PL15220WXL	F6010135
Siena Oak Honey	PL15221WXL	F6010143
Siena Oak Nature	PL15011WL	F6010115
Venice Terrazzo Grey	PL15413SXL	F01CT60 (white)



Shadow Oak Brown

Shadow Oak Nature

Vibrant Oak Beige

Vintage Oak Brown

Vivid Oak Nature

FOR DESIGN FLOORING

wineo 400 Design Fits to 16/60 (Decor art. no.) Art. no. Authentic Oak Brown DB296WXL | RLC296WXL | MLD296WXL F6010122 Balanced Oak Brown DB285WXS | DB285WL | RLC285WL | MLD285WL F6010113 Balanced Oak Grey DB287WL | RLC287WL | MLD287WL F6010128 **Balanced Oak Lightgrey** DB286WXS | DB286WL | RLC286WL | MLD286WL F6010153 Calm Ash Beige DB290WXL | RLC290WXL | MLD290WXL F6010140 F6010132 **Coast Pine Greige** DB280WL | RLC280WL | MLD280WL Coast Pine Taupe DB284WL | RLC284WL | MLD284WL F6010119 Comfort Oak Brown DB293WXL | RLC293WXL | MLD293WXL F6010110 Comfort Oak Dark DB299WXL | RLC299WXL | MLD299WXL F6010121 **Comfort Oak Mellow** DB129WXL | RLC129WXL | MLD129WXL F6010102 Comfort Oak Nature DB291WXL | RLC291WXL | MLD291WXL F6010110 Comfort Oak Taupe DB300WXL | RLC300WXL | MLD300WXL F6010148 Cool Walnut Dark DB298WXL | RLC298WXL | MLD298WXL F6010121 Country Oak Nature DB294WXL | RLC294WXL | MLD294WXL F6010124 Easy Oak Greige DB288WXL | RLC288WXL | MLD288WXL F6010151 Joy Oak Tender DB126WXL | RLC126WXL | MLD126WXL F6010107 Limed Oak Silver F6010123 DB301WXL | RLC301WXL | MLD301WXL DB289WXL | RLC289WXL | MLD289WXL F6010140 Nordic Maple Cream Plain Oak Beige DB281WXS | DB281WL | RLC281WL | MLD281WL F6010155

DB295WXL | RLC295WXL | MLD295WXL

DB292WXL | RLC292WXL | MLD292WXL

DB297WXL | RLC297WXL | MLD297WXL

DB283WXS | DB283WL | RLC283WL | MLD283WL

DB282WL | RLC282WL | MLD282WL

F6010108

F6010154

F6010139 F6010109

F6010112

SKIRTING BOARDS

FOR DESIGN FLOORING

wineo 600

www.blauer-engel.de/uz176

WINCO OOO		
Design	Fits to (Decor art. no.)	16/60 Art. no.
#AmsterdamLoft	DB195W6 RLC195W6	F6010112
#BarcelonaLoft	DB191W6 RLC191W6	F6010134
#BerlinLoft	DB200W6 RLC200W6	F6010150
#BrooklynFactory	DB206W6 RLC206W6	F01CT60 (white)
#CamdenFactory	DB202W6 RLC202W6	F01CT60 (white)
#ChelseaFactory	DB203W6 RLC203W6	F01CT60 (white)
#CopenhagenLoft	DB189W6 RLC189W6	F6010132
#CozyPlace	DB186W6 RLC186W6	F6010130
#ElegantPlace	DB187W6 RLC187W6	F6010123
#LisbonLoft	DB192W6 RLC192W6	F6010107
#LondonLoft	DB193W6 RLC193W6	F6010149
#MilanoLoft	DB190W6 RLC190W6	F6010141
#ModernPlace	DB188W6 RLC188W6	F01CT60 (white)
#MoscowLoft	DB198W6 RLC198W6	F6010135
#NaturalPlace	DB183W6 RLC183W6	F6010154
#NewtownFactory	DB204W6 RLC204W6	F01CT60 (white)
#NewYorkLoft	DB197W6 RLC197W6	F6010137
#NoordFactory	DB201W6 RLC201W6	F01CT60 (white)
#ParisLoft	DB199W6 RLC199W6	F6010105
#SmoothPlace	DB185W6 RLC185W6	F6010126
#SoHoFactory	DB205W6 RLC205W6	F01CT60 (white)
#SydneyLoft	DB194W6 RLC194W6	F6010112
#ViennaLoft	DB196W6 RLC196W6	F6010102
#WarmPlace	DB184W6 RLC184W6	F6010149



 (\mathbf{f})

FOR DESIGN FLOORING

wineo 800

Design	Fits to (Decor art. no.)	16/60 Art. no.
Bergamo Walnut Dark	DB840WXL MLD840WXL	F01CT60 (white)
Bergen Marble Grey	DB853SXL	F01CT60 (white)
Bradford Oak Honey	DB835WXL MLD835WXL	F6010154
Catania Pine Grey	DB841WXL MLD841WXL	F6010152
Chicago Concrete Dark	DB852SXL	F01CT60 (white)
Clifton Oak Brown	DB822WL	F6010116
Dalen Oak Lightgrey	DB830WXL MLD830WXL	F6010132
Dalen Oak Nature	DB834WXL MLD834WXL	F6010154
Dublin Oak Brown	DB838WXL MLD838WXL	F6010122
Lundby Maple Beige	DB831WXL MLD831WXL	F01CT60 (white)
Malmö Oak Beige	DB832WXL MLD832WXL	F6010115
Merano Oak Brown	DB819WL	F6010129
Merano Oak Nature	DB818WL	F6010124
Narvik Oak Nature	DB836WXL MLD836WXL	F6010144
Palermo Oak Brown	DB837WXL MLD837WXL	F6010126
Romo Concrete Lightgrey	DB850SXL	F01CT60 (white)
Sheffield Concrete Grey	DB851SXL	F01CT60 (white)
Stavanger Oak Brown	DB839WXL MLD839WXL	F6010108
Stavanger Oak Nature	DB833WXL MLD833WXL	F6010141
Stockholm Oak Brown	DB820WL	F6010126
Stockholm Oak Taupe	DB816WL	F6010111
Trondheim Oak Brown	DB817WL	F6010107
Visby Oak Cream	DB815WL	F01CT60 (white)
York Oak Brown	DB821WL	F6010137

AUER ENGR

www.blauer-engel.de/uz176



SKIRTING BOARDS | EXTERNAL CORNERS | INSIDE CORNERS | WELD RODS

- available for all wineo 1500 roll designs
- uniform rounding due to machine-finished reinforcement
- very robust no additional supporting profile
- high stability in corner area, no maintenance joint
- elastic material compensates screed sink
- practical skirting dimensions from 2.40 m long no customising of strips
- flush thresholds guaranteed
- materials do not need to be heated during installation

 no additional templates order-specific article 	required				
Technical characteristics	Skirting boards	External corners	Inside corners	Welding rods	
Height	100 mm	100 mm	100 mm	4 mm	
Width	100 mm	100 mm	100 mm	4 mm	
Length	2400 mm	230 mm per site	210 mm per site	60 m / Roll	

Design	Fits to		Skirting board	External corner	Inside corner	Welding rods
Almond Beige	PLR375C		PH375	PEA375	PEI375	PS375
Aloe Green	PLR380C		PH380	PEA380	PEI380	PS380
Apple Green	PLR185C		PH185	PEA185	PEI185	PS185
bright.one	PLR115C		PH115	PEA115	PEI115	PS115
bright.two	PLR116C		PH116	PEA116	PEI116	PS116
bright.three	PLR117C		PH117	PEA117	PEI117	PS117
bright.four	PLR118C		PH118	PEA118	PEI118	PS118
Cherry Red	PLR387C		PH387	PEA387	PEI387	PS387
Chocolate Brown	PLR384C		PH384	PEA384	PEI384	PS384
cool.one	PLR107C		PH107	PEA107	PEI107	PS107
cool.two	PLR108C		PH108	PEA108	PEI108	PS108
cool.three	PLR109C	and the second	PH109	PEA109	PEI109	PS109
cool.four	PLR110C		PH110	PEA110	PEI110	PS110
Cotton Beige	PLR383C		PH383	PEA383	PEI383	PS383
Durban Oak Brown	PLR392C	the star of the	PH392	PEA392	PEI392	PS392
Durban Oak Taupe	PLR391C		PH391	PEA391	PEI391	PS391
Fine Oak Brown	PLR15202W		PH15202	PEA15202	PEI15202	PS15202
Fine Oak Light	PLR15203W		PH15203	PEA15203	PEI15203	PS15203
Fountain Blue	PLR376C		PH376	PEA376	PEI376	PS376
Halifax Oak Brown	PLR390C		PH390	PEA390	PEI390	PS390
Halifax Oak Natural	PLR389C		PH389	PEA389	PEI389	PS389

Design	Fits to	
Honey Mustard	PLR128C	
Jade Green	PLR373C	
Light Grey	PLR021C	
Mayfield Oak Nature	PLR15213W	
Mayfield Oak Taupe	PLR15214W	
Melange	PLR003C	
Melbourne Oak Brown	PLR396C	and the
Melbourne Oak Natural	PLR395C	-
Napa Walnut Brown	PLR136C	- Contraction
Napa Walnut Rust	PLR388C	
Navi Blue	PLR129C	
Newport Oak Brown	PLR394C	
Newport Oak Natural	PLR393C	
Ocean Blue	PLR381C	
Powder Rose	PLR374C	
Pure White	PLR025C	
pure.one	PLR111C	
pure.two	PLR112C	
pure.three	PLR113C	
pure.four	PLR114C	
Royal Blue	PLR385C	
Rust Brown	PLR382C	
Siena Oak Brown	PLR15220W	77-0-1
Siena Oak Honey	PLR15221W	-
Silver Grey	PLR022C	
Springtime Orange	PLR378C	5.5
Steel Grey	PLR023C	
Summer Sky	PLR014C	
Sunshine Yellow	PLR377C	
Tropical Orange	PLR386C	
warm.one	PLR119C	-
warm.two	PLR120C	
warm.three	PLR121C	
warm.four	PLR122C	
Wheat Brown	PLR379C	1 20

	Skirting board	External corner	Inside corner	Welding rods
	PH128	PEA128	PEI128	PS128
	PH373	PEA373	PEI373	PS373
100	PH021	PEA021	PEI021	PS021
73	PH15213	PEA15213	PEI15213	PS15213
10.	PH15214	PEA15214	PEI15214	PS15214
	PH003	PEA003	PEI003	PS003
	PH396	PEA396	PEI396	PS396
-	PH395	PEA395	PEI395	PS395
	PH136	PEA136	PEI136	PS136
	PH388	PEA388	PEI388	PS388
	PH129	PEA129	PEI129	PS129
	PH394	PEA394	PEI394	PS394
12	PH393	PEA393	PEI393	PS393
	PH381	PEA381	PEI381	PS381
	PH374	PEA374	PEI374	PS374
	PH025	PEA025	PEI025	PS025
	PH111	PEA111	PEI111	PS111
	PH112	PEA112	PEI112	PS112
10	PH113	PEA113	PEI113	PS113
	PH114	PEA114	PEI114	PS114
	PH385	PEA385	PEI385	PS385
1	PH382	PEA382	PEI382	PS382
	PH15220	PEA15220	PEI15220	PS15220
	PH15221	PEA15221	PEI15221	PS15221
	PH022	PEA022	PEI022	PS022
	PH378	PEA378	PEI378	PS378
	PH023	PEA023	PEI023	PS023
	PH014	PEA014	PEI014	PS014
	PH377	PEA377	PEI377	PS377
	PH386	PEA386	PEI386	PS386
	PH119	PEA119	PEI119	PS119
	PH120	PEA120	PEI120	PS120
	PH121	PEA121	PEI121	PS121
	PH122	PEA122	PEI122	PS122
	PH379	PEA379	PEI379	PS379

INSTALLATION TOOLS

Rubber hammer | Art. no. 20021004



Blue Marlin knife | Art. no. 20021003



■ the essential tool for professionals – the rubber hammer

Assembly aid pro | Art. no. 10030652

 the professional knife for installing flooring (supplied without blade)

with practical handle – makes installing click-in flooring easier





Windmöller GmbH info@wineo.de www.wineo.de

Member of



