

URKUNDE

Windmöller GmbH
32756 Detmold, Deutschland

wird aufgrund des Zeichenbenutzungsvertrages Nr. 34029 zur DE-UZ 156
Ausgabe 2019 das Recht verliehen, für das Produkt

wineo Sound Reduct Layer SRL gemäß Anhang

das nachstehend abgebildete Umweltzeichen als Ausweis für die besondere
Umweltfreundlichkeit zu führen.



Bonn, den 06. August 2025

R. Wollmann

Geschäftsführer
RAL gGmbH



Bundesministerium
für Umwelt, Klimaschutz, Naturschutz
und nukleare Sicherheit





RAL gemeinnützige GmbH
Fränkische Straße 7
53229 Bonn - Germany

**Anhang zum Vertrag: wineo Sound Reduct Layer SRL gemäß Anhang zum Vertrag,
(Stand: 09.12.2021)**

Wineo Sound Protect Eco+/ SD

Wineo Sound Protect Eco Profi / SD

Wineo Silent Comfort

Wineo Silent Premium

Planeo

Wineo Silent Plus

Wineo Silent Rigid

Wineo SoundStop

Wineo soundPROTECT Special SD 4,0

wineo silentRIGID COMPACT

Wineo Silent Premium Contract 1,8mm /2,6kg/m³

Bezeichnung	Dicke [mm]	Flächengewicht [kg/m ²]
SRL 110 S (SPC)	0,9	1,1
SRL 110 S / SD	2,0	1,1
SRL 130 C	1,5	1,3
SRL 130 S / SD	1,5	1,3
SRL 130 S / SD (AB)	2,0	1,3
SRL 140 S / SD (1,4)	1,4	1,4
SRL 140 S / SD	1,8	1,4
SRL 150 S (SPC)	1,2	1,5
SRL 150 S (1,4 S)	1,4	1,5
SRL 150 S (1,4 V)	1,4	1,5
SRL 150 S (LVT)	1,5	1,5

SRL 150 SD (S)	1,5	1,5
SRL 150 S / SD (W)	1,5	1,5
SRL 150 S (1,5 S)	1,5	1,5
SRL 150 S / SD (1,8)	1,8	1,5
SRL 150 S / SD (MW)	1,9	1,5
SRL 160 S / SD	2,0	1,6
SRL 160 S (H)	2,0	1,6
SRL 170 S	1,65	1,65
SRL 170 S / SD (H)	1,9	1,7
SRL 170 SD	2	1,7
SRL 175 S / SD	2,25	1,75
SRL 180 S Entkopplung	1,6	1,8
SRL 190 S / SD	2,0	1,9
SRL 190 S / SD (TH)	2,15	1,9
SRL 200 C	1,8	2,0
SRL 200 S	1,8	2,0
SRL 200 S / SD (CP)	2,5	2,0
SRL 200 G (WM)	1,9	2,0
SRL 200 G SK	1,9	2,0
SRL 200 G SK (WM)	2,0	2,0
SRL 200 G	2,0	2,0
SRL 200 S – SK (LVT)	2,0	2,0
SRL 200 G – SK (E)	2,1	2,0
SRL 220 C	2,3	2,2
SRL 220 C (MW)	2,3	2,8

SRL 220 S / SD	2,6	2,2
SRL 220 S (2,3)	2,3	2,2
SRL 220 S / SD (2,4)	2,4	2,2
SRL 240 S / SD	2,8	2,4
SRL 260 S	3,4	2,6
SRL 260 S – SK (LVT)	1,8	2,6
SRL 260 SD	3,0	2,6
SRL 265 S / SD	3,0	2,65
SRL 280 S / SD	2,8	2,8
SRL 280 S (E)	2,8	3,0
SRL 280 SD	3,0	2,8
SRL 285 S	3,0	2,85
SRL 285 SD	3,2	2,85
SRL 300 CT	3,0	3,0
SRL 510 S / V	4,0	5,10
SRL 320 SD	4,0	3,2

CERTIFICATE

Windmöller GmbH
32756 Detmold, Germany

is granted the right, on the basis of the contract on the use of the environmental label no. 34029 based on DE-UZ 156 Edition 2019, for the product

wineo Sound Reduct Layer SRL gemäß Anhang

to use the Blue Angel Ecolabel shown below as a sign of special environmental friendliness.



Bonn, 06 August 2025

R. Wollmann

Managing Director
RAL gGmbH



Bundesministerium
für Umwelt, Klimaschutz, Naturschutz
und nukleare Sicherheit





RAL gemeinnützige GmbH
Fränkische Straße 7
53229 Bonn - Germany

**Anhang zum Vertrag: wineo Sound Reduct Layer SRL gemäß Anhang zum Vertrag,
(Stand: 09.12.2021)**

Wineo Sound Protect Eco+/ SD

Wineo Sound Protect Eco Profi / SD

Wineo Silent Comfort

Wineo Silent Premium

Planeo

Wineo Silent Plus

Wineo Silent Rigid

Wineo SoundStop

Wineo soundPROTECT Special SD 4,0

wineo silentRIGID COMPACT

Wineo Silent Premium Contract 1,8mm /2,6kg/m³

Bezeichnung	Dicke [mm]	Flächengewicht [kg/m ²]
SRL 110 S (SPC)	0,9	1,1
SRL 110 S / SD	2,0	1,1
SRL 130 C	1,5	1,3
SRL 130 S / SD	1,5	1,3
SRL 130 S / SD (AB)	2,0	1,3
SRL 140 S / SD (1,4)	1,4	1,4
SRL 140 S / SD	1,8	1,4
SRL 150 S (SPC)	1,2	1,5
SRL 150 S (1,4 S)	1,4	1,5
SRL 150 S (1,4 V)	1,4	1,5
SRL 150 S (LVT)	1,5	1,5

SRL 150 SD (S)	1,5	1,5
SRL 150 S / SD (W)	1,5	1,5
SRL 150 S (1,5 S)	1,5	1,5
SRL 150 S / SD (1,8)	1,8	1,5
SRL 150 S / SD (MW)	1,9	1,5
SRL 160 S / SD	2,0	1,6
SRL 160 S (H)	2,0	1,6
SRL 170 S	1,65	1,65
SRL 170 S / SD (H)	1,9	1,7
SRL 170 SD	2	1,7
SRL 175 S / SD	2,25	1,75
SRL 180 S Entkopplung	1,6	1,8
SRL 190 S / SD	2,0	1,9
SRL 190 S / SD (TH)	2,15	1,9
SRL 200 C	1,8	2,0
SRL 200 S	1,8	2,0
SRL 200 S / SD (CP)	2,5	2,0
SRL 200 G (WM)	1,9	2,0
SRL 200 G SK	1,9	2,0
SRL 200 G SK (WM)	2,0	2,0
SRL 200 G	2,0	2,0
SRL 200 S – SK (LVT)	2,0	2,0
SRL 200 G – SK (E)	2,1	2,0
SRL 220 C	2,3	2,2
SRL 220 C (MW)	2,3	2,8

SRL 220 S / SD	2,6	2,2
SRL 220 S (2,3)	2,3	2,2
SRL 220 S / SD (2,4)	2,4	2,2
SRL 240 S / SD	2,8	2,4
SRL 260 S	3,4	2,6
SRL 260 S – SK (LVT)	1,8	2,6
SRL 260 SD	3,0	2,6
SRL 265 S / SD	3,0	2,65
SRL 280 S / SD	2,8	2,8
SRL 280 S (E)	2,8	3,0
SRL 280 SD	3,0	2,8
SRL 285 S	3,0	2,85
SRL 285 SD	3,2	2,85
SRL 300 CT	3,0	3,0
SRL 510 S / V	4,0	5,10
SRL 320 SD	4,0	3,2